



POLYMER PROTECTIVE COATING

Poly Magic Polymer Protective Coating can be used on wet or dry exterior surfaces and provides a long-lasting shine to clearcoats and plastic surfaces. Enhances rubber side molding and trim, without blushing or whitening. Formulated to be static resistant and provides UV protection. VOC compliant formula. *Sprayer sold separately*.

#63-QT - 32oz. Bottle

FEATURES

- Brilliant, long-lasting shine
- Fast spray-on, wipe-off
- Static resistance repels dust
- UV protection
- 50 State VOC compliant

IDEAL FOR PREPARING NEW CAR PURCHASES FOR EXPRESS CLIENT DELIVERY!



Product Description	Poly Magic is a super-quick high-gloss polymer finishing spray for use on exterior surfaces, that provides a lasting shine to exterior paint, plastic and chrome. Enhances rubber side molding and trim without blushing or whitening. Nonabrasive. Easy to use; just apply to exterior surfaces, wipe on then wipe off. Use after every wash to maintain a showroom finish.	
Directions	 Shake well. Lightly mist product onto the surface. Immediately wipe product into the exterior surfaces using soft towel. Allow polymer product to come to a slight haze. Wipe or buff to a high-gloss with a second towel that is clean, soft and DRY to remove any excess product. For optimal performance, use on a vehicle that has been properly cleaned and dried. This product can be used on a slightly damp surface as well. NOTE: The haze will be slight as this product is a polymer, not a traditional carnauba wax. To avoid streaking, it is best to remove product once hazed. Use only a small amount of product, or enough to spread over applied area. Do not use on a HOT SURFACE. 	
Surface Applications	For express, deep, high-gloss, and added surface protection of clearcoat, single stage, acrylic, lacquers, enamels, as well as powder-coated paints. Also, performs well on exterior chrome plastic and rubber.	
Additional Uses	Excellent on RVs, boats, motorcycles, bikes, and other painted and clearcoat surfaces.	
Helpful Tips	To ensure the highest performance of #63-QT Poly Magic it is best to remove all surface contamination with Clay Magic® #2200 fine detailing clay prior to application. Do not apply 63-QT in thick layers. Do not apply to hot surfaces. Product can be used in the sunlight if the surface is not hot.	
Technical	Product Category Color	Waxes, Polymers & Sealants Light Blue
	Scent Abrasiveness (1-10 with 10 being highest amount of abrasiveness)	Solvent 0
Safety	Read all directions and warnings prior to using Auto Magic products. Safety Data Sheets can be found online at automagic.com.	

